

# SoyGuard® Wood Protection

Protects wood for two years

Easy one-coat application

Safe for family, pets and the environment

Slightly darkens and enhances  
natural beauty of wood

Low odor (Ultra Low VOC)

Patented, mildew resistant finish

Easy soap and water clean-up

[www.SoyGuard.com](http://www.SoyGuard.com)

BIO  
PRESERVE

1540 East Lake Road • Erie, PA 16511  
1-800-416-9511 • [info@soyguard.com](mailto:info@soyguard.com)

For more information about SoyGuard®,  
visit [www.SoyGuard.com](http://www.SoyGuard.com).

# SoyGuard® Wood Protection



## Premium Water Repellent & Sealer

*Natural Soy-based Waterproofing  
Finish for Exterior Wood*



## Protects wood. And a whole lot more.

SoyGuard® Premium Water Repellent & Sealer is the only exterior wood finish that combines superior performance with inherent safety for children, pets, and plants. Created from a natural solvent derived from soybean oil, SoyGuard deeply penetrates wood surfaces to coat wood cells with a protective polymer resin. It's a safe alternative to flammable and toxic wood coatings containing chemicals known to cause cancer and birth defects. SoyGuard has a low odor and provides a mildew resistant finish that slightly darkens and enhances the natural beauty of wood.

### Proven performance.

Independent testing confirms that our patented formula not only exceeds industry standards for anti-swelling and waterproofing, but also provides better overall water repellency than the leading solvent-based, clear water repellents.\* Surfaces treated with one coat of SoyGuard are protected against swelling, warping, cracking and checking for up to two years.



\*Test results based on comparative analysis outlined in ASTM D 5401 and ASTM D 4446.



### Directions for use.

SoyGuard is recommended for all new, old and pressure-treated exterior wood surfaces including outdoor decks, siding, furniture, fences, sashes, doors and millwork. It may be used as a primer or stand-alone finish.

#### *Surface preparation.*

SoyGuard may be applied directly to any clean, dry wood surface free of wax, varnish or other coatings. For best results, clean wood that has been weathered or darkened by mildew to remove discoloration. No preliminary coating is necessary.

#### *One coat application.*

Apply only one thin coat using any standard brush or paint pad (back-brushing may be required if using a roller or spray equipment) at a rate the surface will absorb. SoyGuard is mildew resistant, but if the wood surface is subject to heavy mold growth, a mildewcide can be added to the solution. Best if applied above 50°F. May slightly darken wood.

#### *Coverage and drying time.*

One gallon will protect a surface up to 250 square feet depending on properties of the wood, including age, surface type, and porosity, as well as the method of application. Allow eight to 12 hours before foot traffic to ensure the product is thoroughly dried (dry time will be affected by species, porosity and moisture content of the wood, weather and atmospheric conditions). Allow two weeks before painting surfaces treated with SoyGuard.

